



POLTYS DCC AND WIRELESS PULL CORDS

How Does DCC Improve My Facility?

- **Increased Mobility** - Caregivers can receive alerts no matter where they are in your building
- **Shorter wait times:** Use reports to improve caregiver response time
- **Proactive Monitoring** - Admins and/ or owners can be notified by email or text message if a call for help is not answered
- **Atmosphere** - No noisy bells means a more home-like environment for residents
- **Market Your Community** - Show incoming families how good your caregiving services are

Polty's **Direct Care Connect™ (DCC)** provides wireless pull cords for seamless connectivity of residents with caregiving staff in case of emergency.

Polty's Wireless Pull Cord is an affordable surface-mounted call station that provides full supervision and low maintenance costs.

When used with the Polty's DCC, the device provides wireless emergency assistance notification to caregivers.

The wireless pull cords are frequently installed in nursing homes, assisted living residences, and other health care centers.

DCC INTEGRATION

Polys DCC directly integrates with many wireless sensors, industry-standard Nurse Call Systems and Fire Alarm Systems.

- Pendants, pull cords, and other wireless sensors
- Panasonic KX-DTU100
- Dukane
- Conexall
- Rauland
- Eiris – TAP
- Telergy – TAP
- Austco – UDP
- COMP2, w/ Cancel, w/ Location, over TCP
- COMP2 over IP for SARA
- NCS3
- ESPA 4.1 protocol for Courtney-Thorne and Intercall systems
- UK market – ESPA, APR, Quantec, MCD, Protek
- Roam Alert
- PBX Sensors
- Cornell
- Servowatch
- MCD, MCD Logger
- Gent by Honeywell

TEXT NOTIFICATION

The alarm notifications are sent to DECT phones and mobile devices as text messages.

Caregivers can select whether to accept, reject or call back the resident just by pressing predefined buttons on the DECT phone keypad/ mobile device display.

MOBILE NOTIFICATION BY DCARE CONNECT

Polys DCare™ Messenger is the application and service that sends audio messages recorded at runtime (i.e. Push-toTalk mode) and text alarms using the mobile device.

Voice and text alarms are received by mobile caregivers predefined in DCC.

Text alarms are displayed on the caregiver mobile device.

Polys DCare™ Messenger application and service is compatible with Google Android smartphones and tablets.

CAREGIVER LOCATION TRACKING

DCC may track caregiver location (i.e. Android mobile phone) within the caregiving facility.

The locations are identified using Bluetooth Low Energy (BLE) beacon devices. Each room/ location is stuffed with one/ two BLE beacons.

DCC KEY FEATURES

- Compatible with Panasonic KX-NSX/ NS/ TDE/ NCP/ TDA PBX series
- Dispatch the Bed Stations alarms to appropriate caregiving staff wirelessly
- Work on either Wi-Fi, GSM, LTE or UMTS cellular networks
- Send voice alarms recorded at runtime using mobile device by Push-to-Talk mode
- Send text alarms using the mobile device
- Text alarms are received by caregivers' mobile devices configured in DCC
- Text alarms are displayed on the caregiver's mobile device
- Caregiver may accept, reject, or call a predefined phone number by tapping specific buttons on mobile device
- Mobile client application for Android devices
- Can work independently or integrate with the existing telephony system in place

DCC PULL CORD HARDWARE

- Wireless Pull Cord station with One-Way Binary RF Module
- Panasonic CR123A lithium battery (not included)



www.polys.com
sales@polys.com
support@polys.com

If you want information about above solution, please contact the above address. Design and specifications are subject to change without notice. All trademarks and trade names are those of their respective owners. Your access to this document should not be construed as granting, by implication, estoppel or otherwise, any license or right to use any marks appearing in this document without the prior written consent of Polys or of the applicable third-party owner thereof. You acknowledge that you do not acquire any ownership rights by printing or downloading this copyrighted material.

DISTRIBUTED BY